ALFA X

Portable Compound Radial Saw with Tabletop Ø 305 mm





FEATURES

Used for cutting processes of aluminum, plastic and wooden materials.

- Cutting at any desired angle between -45° and +45° 0°, 5°, 10°, 15°, 20°, 22,5°, 25°, 30°35°, 40 , 45° right and left angle fixing
- Head with ability to tilt left between 0° and 45° (Performs tilt cutting when lower plate is at 0 (Zero) position)
- Laser Guide for accurate cuts
- Screw workpiece clamp
- Anti vibration foots

STANDARD EQUIPMENT

• Screw workpiece clamp


OPTIONAL EQUIPMENT


- Stand
- Ø 305 mm saw blade
- Conveyor
- Brake System
- Three-phase system
- Profile gauge



WEB


Upper Table














| 85 | | | | 300Ø |
|-----|-----|--------|-------|----------|
| | | | | |
| | | 45° | 22,5° | 0° (90°) |
| | | | // | |
| | | | | |
| 0 1 | 220 | 290 31 | 5 | 450 |
| 40 | | | | 300Ø |
| .0 | | | | |
| | | | | |
| 0 | | 3 | 15 | 450 |

| | | | | h | | S. C. | SK kg | | | | | |
|--|------------|---------------|----------|---------|-----------|---|-----------|---------------|-----------|----------|----------------|-----------------------------|
| | HP kW | | Hz | (230 V) | ø D | ø d | | | | h | 45° | l x w x h (mm) |
| | 1,5 1,1 | 3000 r.p.m | 50 60 | 5 A | 305 mm | 30-32 mm | 3,2 mm | 3000 r.p.m | 160 mm | 40 mm | 40 x 315 mm | 570 x 1030 x 685 35,5 kg |