

LEO R

Automatic Front Blade Saw Ø 550 mm - 2 Axis Servo Controlled





YouTube








WEB



LEO-R, automatic front blade saw with 2 axis servo controlled and 550 mm saw is ideal for cutting aluminum and PVC profiles with different angles and thickness. LEO-R designed for cutting wider profiles with the servo motion system, automatic positioning at all degrees between $-22,5^\circ$ and 45° allows for perfect cutting operation. Safety is a topmost priority for LEO-R together with the horizontal clamps and the vertical clamp along with profile protective shield which improve the cutting quality.



																		
HP	kW	n	Hz	I	(220/400)	kW	n	I	ø D	ø d	s	n	min.	max.	Air Pressure	Air Consumption	l x w x h (mm)	
4	3	3000	50	11,5/6,4	A	0,8	3000	5,02	A	550	30-32	4,4	2430	395	3350	6 - 8 bar	30 L / min.	7310 x 1985 x 1580
		r.p.m	60							mm	mm	mm	r.p.m				780 kg	



LEO R

Automatic Front Blade Saw Ø 550 mm - 2 Axis Servo Controlled

FEATURES

Rapid angle positioning of heads with servo control at any angles between	-22,5° and 45°
Maximum internal rotation angle	45°
Maximum external rotation angle	-22,5°
Hydro-pneumatic cutting feed adjustment	●
Cemented carbide saw blade	1
Saw blade diameter	550 mm
Saw blade motor power	3 kW - 4 HP
Cutting zone protection covers	●
Horizontal pneumatic clamps	●
Vertical pneumatic clamp	●
Spray saw cooling system	●
Digital adjustment saw blade travel distance	●
Saw blade travel speed adjustment	●
Barkod writer	●
Data transfer via remote network connection, ethernet and USB	●
10" Touchscreen	●
Digital Conveyor	●
Vacuum cleaner for chips	○
Oz Machine Softcut (Cutting optimisation program)	○

● Standard ○ Opsiyonal

