


LEPUS - X


CNC ACP Processing Machine (3 Axis)






The 3-Axis CNC controlled panel and profile processing machine LEPUS - X is developed to cut v - channel opening and similar operations on various composite panels and plates. Thanks to its automatic tool magazine system with capacity for 5 tools, LEPUS -X saves time when switching to different operations. In addition, LEPUS X enables processing of aluminum, wooden, plastic and various materials by replacement of the milling cutter.









LEPUS - X

CNC ACP Processing Machine (3 Axis)



MACHINING LENGTHS	
X Axis (Longitudinal)	4000 mm
Y Axis (Lateral)	1600 mm
Z Axis (Vertical) – without tool	250 mm
Insertable Panel Dimensions Min./Max.	500 x 300 mm / 4000 x 1600 mm
POSITIONING SPEED	
X Axis (Longitudinal)	55 m/min
Y Axis (Lateral)	55 m/min
Z Axis (Vertical)	15 m/mir
SPINDLE MOTOR	
Motor Power	7.5 kW
Motor rotation speed	24000 rpm
Tool Holder	ISO 30
Cooling Type	Elektro Fan
TOOL DIAMETER	
Carbide Milling Cutter	5 mm
Grout Milling Cutter	10 mm
DUST EXTRACTION MOTOR (VELA)	
Motor Power	3 kW
Motor Rotation Speed	3000 rpm
Air Flow	700 m3 / h
VACUUM MOTOR X 2	
Motor Power	7,5 kW
Motor Rotation Speed	3000 rpm
CONTROL UNITS	
CNC control unit	
Data transfer from PC via CF card, USB flash drive or remote network connection	•
Industrial PC - Touch Screen	15" HM
AIR - ELECTRIC	
Voltage	400 V
Maximum Power	38 kW
Frequency	50 - 60 Hz
Pressure	6-8 bar
OPERATIONAL AREA	
Dust Extraction System	
External Button Controlled Vacuum Zones/ Vacuum in independent areas	
Automatic Tool Length Measurement	
X and Y Axis Reference Stop	
Handwheel Control For Manual Movement And Adjustments	
Laser Safety Barrier	
Metal Barriers On Three Sides Blocking Access To The Work Area	•
Spare ISO 30 Tool Holder	C
Spare Tool Holder Pens	
Lubricated Vacuum Pump	C
Maximum tool storage system number	5
Alphacam CAD/CAM Software	

o Opsiyonal Standard