GARNET XS4 8000

CNC Profile Machining Center (4 Axis)

özçelik

Automation by FANUC

PRODUCT WEB LINK

WEB

The 4-axis CNC machining center, GARNET XS 4 8000, boasts a versatile spindle that tackles a wide range of materials, including aluminum, PVC, light alloys, and even steel. With its ability to operate between -90° and +90°, the GARNET XS 4 8000 tackles profiles of various sizes. This all-in-one powerhouse streamlines milling, water channel opening, punching, marking, and end milling for diverse materials, excelling at both standard and non-standard operations. An impressive working area of 320 mm x 255 mm further enhances user experience by enabling efficient processing.

By focusing on providing convenient solutions for customers, and combining power and precision, GARNET XS4 8000 lets the processing capacity be only limited by the users imagination, thanks to the 5.6 kW spindle motor with automatic tool replacement feature.

Thanks to its built-in automatic magazine with capacity for 16 tools, GARNET XS4 8000 saves time when switching to different operations.The GARNET XS4, which positions its clamps ful-ly automatically using the X-axis, completely takes on the user's workload.

Double-Linear Guide bridge systems have are more rigid and durable compared to single-Line-ar Guide bridge systems. Reduced vibration and allows for more precise processing of the profiles.



Maintenance of transmission elements is accomplished by the automatic lubrication system which is offered as an optional feature increasing the service life for accuracy in processes. Capaci-ty may be varied for processing of non-standard profiles with on demand optimization of size and number of clamps.







+90 0216 304 20 10 info@ozcelik.com Anadolu Mh. Kanuni Cd. 8, 34956 Tuzla, İSTANBUL - TÜRKİYE

GARNET XS4 8000

CNC Profile Machining Center (4 Axis)

özçelik

MACHINING LENGTHS	
X Axis (Longitudinal)	8000 mm
Y Axis (Lateral)	320 mm
Z Axis (Vertical)	255 mm
A Axis (Head processing angles)	-90° / +90°
POSITIONING SPEED	
X Axis (Longitudinal)	90 m/min
Y Axis (Lateral)	60 m/min
Z Axis (Vertical)	20 m/min
A Axis (Rotational Movement)	166° /sec
AIR	
Pressure	6-8 Bar
ELECTRICAL	
Max. Power	8 kW
Voltage	400V 3P, N, PE AC
Frequency	50-60 Hz
SPINDLE	
Max. Power	5.6 kW
Maximum rotation speed	20.000 r.p.m
Tool holder	HSK F50
Cooling type	Liquid
TOOL STORAGE	
Automatic Linear Type Tools Magazine	●
Maximum tool storage system number	16
Maximum saw blade diameter in to the storage system	150 mm
Automatic Tools Measuring	●
SCREW-CUTTING CAPACITY	
M8 - with compressed tapping head	○
PROFILE POSITIONING	
Right and left pneumatic profile reference alignment	●
CONTROL UNIT	
Industrial PC - Touch Screen	15”
Barcode reader	●
Camquix CAM program	●
CadXtract CAD-CAM Production program	○
OPERATIONAL AREA	
Clamps, standard pcs	8
Clamps, maximum pcs	10
Dual Station operation feature	●
Automatic clamp positioning with the X-axis	●
Spray-Automatic lubrication in processing area	●
Cabinet providing protection in processing zone	●
Automatic Tool cooling system	○
FESTO pneumatic system	○
Side tunnels	●
Additional Clamp	○

● Standard ○ Opsiyonal

Özçelik Makina continuously improves its products and offers new and modern solutions for PVC and Aluminum Profile Processing. Accordingly, Özçelik reserves the right to change the information in this document without notice. All dimensions and weights are reference values. Valid from January 2025